

TSC

The Smarter Choice.



ALPHA-4L – Portable Direct Thermal Label Printer

RUGGED AND RELIABLE MOBILE PRINTING DELIVERS YOUR LABELS WHEREVER YOU NEED THEM



KEY FEATURES

- IP54-rated protective case to resist dust and water
- Plastic design with rubber over-mold construction that withstands 1.5 m (5 ft) drop and endures 1.8 m (6 ft) drop with its protective case
- Ready for EPL, ZPL, ESC-POS or CPCL environments, TSC Droid APP & SDK, WinCE Quick-link tool & SDK, iOS SDK
- Wired & wireless communication interfaces: USB 2.0, RS-232, Bluetooth and 802.11 a/b/g/n
- High capacity 5800 mAh rechargeable Li-ion batteries
- Large paper capacity to reduce the frequency of changing paper roll
- Linerless ready
- High-speed processor and extensive memory for fast print speeds of up to 102 mm (4") per second
- 2-year standard warranty

APPLICATIONS

- Portable point of sale
- Retail item marking, markdowns, shelf labeling & shelf talkers
- Labels for shipping & receiving
- Inventory control
- Cross-docking
- Pick, pack & apply operations
- Print pick tickets
- Logistics receipts

EZS[®]
Etiketten Thermotransferfolien Hard- und Software
IDENTTECHNIK
It's always a good ID

ALPHA-4L – Portable Direct Thermal Label Printer

| PRINTER MODEL | Alpha-4L |
|----------------------------|---|
| Resolution | 8 dots/mm (203 DPI) |
| Printing method | Direct Thermal |
| Max. print speed | 102 mm (4")/second 2, 3 ips for peeler mode |
| Max. print width | 104 mm (4.09") |
| Max. print length | 2,286mm (90") |
| Enclosure | Plastic with rubber over molded |
| Physical dimension | 160 mm (W) x 191.6 mm (H) x 79 mm (D) 6.30" (W) x 7.54" (H) x 3.11" (D) |
| Weight (including battery) | 1.1 kg (2.43 lbs) |
| Drop specification | 1.5 m (5 ft) 1.8 m (6 ft) (w/ IP54-rated protective case) |
| IP rating | IP54 (w/case) |
| Max. roll capacity | 67.3 mm (2.65") OD |
| Processor | 32-bit RISC CPU |
| Memory | <ul style="list-style-type: none"> • 16 MB Flash memory • 32 MB SDRAM • microSD card reader for Flash memory expansion, up to 4 GB |
| Interface | <ul style="list-style-type: none"> • USB 2.0 • Bluetooth • 802.11 a/b/g/n Wireless (factory option) • RS-232 (user option) |
| Power | 7.2V DC, 5800 mAh Li-ion rechargeable battery |
| Operation switch, button | <ul style="list-style-type: none"> • 2 buttons (Power, Feed) & 6 LED indicators (Printer, Battery, Wireless status) - standard • 4 buttons (Power, Feed, Menu, Info) & 2 LED indicators (Power, Error) & 2" LCD display, 128 x 64 pixel w/backlight - factory option |
| Sensors | <ul style="list-style-type: none"> • Black mark reflective sensor • Transmissive gap sensor • Peel sensor • Head open sensor |
| Real time clock | Standard |
| Internal fonts | <ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font |
| Bar code | <ul style="list-style-type: none"> • 1D bar code Code 11, Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN14, EAN128, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, POSTNET, China Post, ITF14, TELPEN, PLANET, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS • 2D bar code Code 49, PDF-417, MicroPDF417, Maxicode, DataMatrix, QR code, Aztec, CODABLOCK F mode, GS1 Databar |
| Printer language | TSPL-EZ (Compatible to EPL, ZPL, ZPL II), ESC-POS or CPCL emulation |
| Media type | Die cut, black mark, receipt, fan-fold, linerless, continuous (outside wound) |
| Media width | 50.8 ~ 112 mm (2.0" ~ 4.4") |
| Media thickness | 0.055 ~ 0.165 mm (2.2 ~ 6.5 mil) |
| Media core diameter | 12.7 ~ 25.4 mm (0.5" ~ 1") |
| Label length | 12.7 ~ 2,286 mm (0.5" ~ 90") 25.4 ~ 152.4 mm (1" ~ 6") for peeler mode |
| Environment condition | Operation: -10 ~ 50 °C (14 ~ 122 °F), 10 ~ 90% non-condensing Storage: -40 ~ 60 °C (-40 ~ 140 °F), 10 ~ 90% non-condensing |
| Safety regulation | FCC, CE, CB, CCC, TÜV, SRRC, BC, NCC |
| Environmental concern | Comply with RoHS, WEEE |
| Accessories | <ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • Belt Clip • Li-ion battery • Power adapter <p>*SDK for iOS (iPhone & iPad), Android 2.2 or higher, WinCE/MM 6.0/6.1pro can be downloaded from website.</p> |
| Limited warranty | <ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first • Battery: 1 year |
| Factory options | <ul style="list-style-type: none"> • 802.11 a/b/g/n Wireless network • 2" LCD display, 128 x 64 pixel w/white LED backlight • Black mark reflective sensor position (default center, right, or left side) • Linerless kit • USB to RS-232 converter cable • USB cable • Li-ion battery |
| User options | <ul style="list-style-type: none"> • IP54-rated protective case • Shoulder strap • Charging station 1 cell or 4 cells (with changeable power connector) • Vehicle power adapter |



TSC
The Smarter Choice.
EZS
Etiketten · Thermotransferfolien · Hard- und Software
IDENTTECHNIK
It's always a good ID



EZS Identtechnik GmbH
Welserstrasse 4
D-87463 Dietmannsried

Tel.: +49 (0)8374 / 234 44
Fax: +49 (0)8374 / 234 45
eMail: info@e-z-s.de
Web: www.e-z-s.de