

# TSC

The Smarter Choice.

## EZS®

Etiketten Thermotransferfolien Hard- und Software

IDENTTECHNIK

It's always a good ID



## ML240P SERIES

### Simplicity and Agility Just One Step Away

TSC ML240P Series is a brand new generation of industrial barcode label printers. The light industrial ML240P Series features ease of use, intuitive color GUI display, noise-reduced printing, and self-diagnostic TPH Care. The ML240P Series has a durable and flexible design and does not require special tools for performing common service and maintenance.

Its compact footprint is perfect for crowded work environments. The ML240P Series is designed for durability while producing high quality printed labels. With its enhanced design and printing algorithm, the noise level from printing operation is dramatically reduced. The adjustable thermal printhead and self-diagnostic TPH Care mechanism ensure optimal print quality regardless of the application or label design.

#### KEY FEATURES



##### Streamlined and Small Footprint Design

- Brand new compact design
- Small footprint fits easily into more spaces and fits in limited operation areas



##### Robust and Agile Design for Optimal Quality

- The combination of rugged die-cast, modularized base and adjustable TPH module design structure optimizes print quality



##### Noise-Reduction Printing Engineering

- Its enhanced design and printing algorithm feature results in a quieter and smoother printing operation



##### Self-Diagnostic TPH Care Mechanism

- An advanced mechanism allows for real-time printhead health status to ensure stable and high quality printouts for maximum cost-effectiveness



##### Effortless User Operation with Color Display

- Wide open angle for easy media handling
- Ease of use 2.3" color GUI display and intuitive indicator



##### One Step Maintenance

- Tool-less removal and replacement of the printhead and platen roller saves time

#### APPLICATIONS



##### Manufacturing

- Work In Process
- Product Marking
- Compliance Labeling



##### Warehouse & Logistics

- Packing
- Order Fulfilment
- Shipping/Receiving
- Inventory Management



##### Healthcare

- Blood Test Tube Label
- Patient Wristband Label



##### Retail

- Product Label
- Event Ticketing

## ML240P SERIES – Industrial Thermal Transfer Bar Code Printer

PRINTER MODEL	ML240P	ML340P
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Printing method	Thermal Transfer & Direct Thermal	
Max. print speed	152 mm (6")/second	127 mm (5")/second
Max. print width	108 mm (4.25")	106 mm (4.16")
Max. print length	25,400 mm (1,000")	11,430 mm (450")
Enclosure	Die-cast print mechanism/Metal cover with large media window	
Physical dimension	248 mm (W) x 245 mm (H) x 330 mm (D) 9.76" (W) x 9.65" (H) x 12.99" (D)	
Weight	7.6 kg (16.76 lbs)	
Label roll capacity	139.7 mm (5.5") O.D., 1" or 1.5" I.D core	
Ribbon	450 m long, max. O.D. 81.3 mm, 1" core (ink coated outside or inside)	
Ribbon width	40 ~ 110 mm (1.6" ~ 4.3")	
Processor	32-bit RISC CPU	
Memory	<ul style="list-style-type: none"> <li>• 128 MB Flash memory</li> <li>• 64 MB SDRAM</li> </ul>	
Interface	<ul style="list-style-type: none"> <li>• RS-232</li> <li>• USB 2.0</li> <li>• Internal Ethernet, 10/100 Mbps</li> <li>• USB host, for scanner or PC keyboard</li> <li>• Internal Bluetooth 4.2 MFi (factory option)</li> <li>• Slot-in 802.11 a/b/g/n wireless (dealer option)*</li> </ul>	
Power	Internal universal switching power supply <ul style="list-style-type: none"> <li>• Input: AC 100-240V, 1.5A, 50-60Hz</li> <li>• Output: DC 24V, 2.5A, 60W</li> </ul>	
Display	<ul style="list-style-type: none"> <li>• 2.3" color LCD</li> <li>• 1 status indicator</li> </ul>	
Operation switch, button	<ul style="list-style-type: none"> <li>• 6 buttons (Menu, Pause/Feed, Up, Down, Left, Right)</li> </ul>	
Sensors	<ul style="list-style-type: none"> <li>• Gap transmissive sensor (position adjustable)</li> <li>• Black mark reflective sensor (position adjustable)</li> <li>• Ribbon end sensor</li> <li>• Head open sensor</li> </ul>	
Real time clock	Standard	
Internal fonts	<ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>	
Bar code	<ul style="list-style-type: none"> <li>• 1D bar code Code 11, Code 39, Code 49, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Standard 2 of 5, Industrial 2 of 5, Interleave 2 of 5, EAN-8, EAN-13, EAN-14, EAN-128, ITF14, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, PLANET, POSTNET, RSS-Stacked, GS1 DataBar, China Post, Telepen, LOGMARS</li> <li>• 2D bar code PDF-417, Micro PDF 417, Maxicode, DataMatrix, QR code, Aztec, TLC 39, RSS</li> </ul>	
Font and barcode rotation	0, 90, 180, 270 degree	
Printer language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)	
Media width	20 ~ 118 mm (0.8" ~ 4.7") 20 ~ 114.3 mm (0.79" ~ 4.5") for peel or cutter mode	
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)	
Media core diameter	25.4 or 38.1 mm (1" or 1.5")	
Label length	5 ~ 25,400 mm (0.2" ~ 1,000")	5 ~ 11,430 mm (0.2" ~ 450")
Environment condition	Operation: 0 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing	
Safety regulation	FCC Class A, CE Class A, RCM Class A, cTUVus, TÜV/safety, CCC, BIS, KC, BSMI, EAC, ENERGY STAR®	
Environmental concern	Comply with RoHS, REACH, WEEE	
Accessories	<ul style="list-style-type: none"> <li>• Windows labeling software CD disk</li> <li>• Quick start guide</li> <li>• USB cable</li> <li>• Power cord</li> </ul>	
Limited warranty	<ul style="list-style-type: none"> <li>• Printer: 2 years</li> <li>• Print head: 25 km (1 million inches) or 12 months which comes first</li> <li>• Platen: 50 km (2 million inches) or 12 months which comes first</li> </ul>	
Factory options	<ul style="list-style-type: none"> <li>• Internal Bluetooth 4.2 MFi</li> </ul>	
Dealer options	<ul style="list-style-type: none"> <li>• Peel-off kit</li> <li>• Regular guillotine cutter (full cut)</li> <li>• 802.11 a/b/g/n wireless module (for device without slot-in housing)*</li> </ul>	
User options	<ul style="list-style-type: none"> <li>• KP-200 Plus keyboard display unit</li> <li>• 802.11 a/b/g/n wireless module (for device with slot-in housing)*</li> </ul>	



Note: \*Either Wireless or Bluetooth interface is available.



Made for  
iPhone | iPad | iPod



**EZS Identtechnik GmbH**  
Welserstrasse 4  
D-87463 Dietmannsried

Tel.: +49 (0)8374 / 234 44  
Fax: +49 (0)8374 / 234 45  
eMail: info@e-z-s.de  
Web: www.e-z-s.de