

TSC

The Smarter Choice.

EZS®

Etiketten Thermotransferfolien Hard- und Software

IDENTTECHNIK

It's always a good ID



PEX-1100

PEX-1200

PEX-1000 SERIES

Igniting Output with the Fastest Print Engine

TSC PRINT ENGINE: FAST, RELIABLE, PROGRAMMABLE

TSC's innovative PEX-1000 Series print engine incorporates a robust die cast construction designed for years of reliability, ease of use, and cost-conscious serviceability. The PEX-1000 Series combines a precision print mechanism with high performance electronics to produce labels at up to 18 inches per second.

Designed for ease of integration, the PEX-1000 Series features a bolt-compatible construction with a commonly used GPIO interface and an easy to use color display. The PEX-1000 Series offers simple integration into both new and existing label application installations. It is ideal for manufacturing and logistic applications where high speed and high demand label printing is required.

KEY FEATURES



Rugged Design

- Durable and reliable, delivers outstanding print quality for every label
- State of the art and robust peel-off capability works with a wide range of label sizes, including excellent small label performance



High Performance

- Highest print speed in its class, up to 18 ips
- With the high precision label positioning, it can print labels as small as 5mm in height.
- Multiple connectivity - Industry Standard GPIO, USB, Parallel, Serial, Ethernet, options including Bluetooth 4.0 & 802.11 a/b/g/n wireless module



Exceptional Usability

- Exclusive color display is intuitive and easy to operate
- USB host in front supports one-step updates for label formats or firmware via USB drive



Ease of Maintenance

- Drawer design in rear for quick access to maintenance parts
- Media drive system is modular design for quick and easy access and replacement



Extensive Compatibility

- Easily mount the print engine into the current applicator and support print language emulation

APPLICATIONS



Manufacturing

- Automotive
- Food and Beverage



Warehouse & Logistics

- Pallet Labeling
- Carton Shipping



Healthcare

- Pharmaceutical labeling

PEX-1000 SERIES – Print Engine

MODEL	LH RH	PEX-1120 PEX-1220	PEX-1130 PEX-1230	PEX-1160 PEX-1260
Resolution		8 dots/mm (203 DPI)	12 dots/mm (300 DPI)	24 dots/mm (600 DPI)
Printing method		Thermal Transfer & Direct Thermal		
Max. print speed		457 mm (18")/second	356 mm (14")/second	152 mm (6")/second
Max. print width		104 mm (4.09")		
Max. print length		25,400 mm (1000")	11,430 mm (450")	2,540 mm (100")
Enclosure		Die-cast based print mechanism		
Physical dimension		245 mm (W) x 300 mm (H) x 390 mm (D) 9.65" (W) x 11.81" (H) x 15.35" (D)		
Weight		13 kg (28.66 lbs)		
Ribbon		600 m long, max. OD 90 mm, 1" core (ink coated outside or inside)		
Ribbon width		25.4 mm ~ 114.3 mm (1" ~ 4.5")		
Processor		32-bit RISC CPU		
Memory		<ul style="list-style-type: none"> • 512 MB Flash memory • 512 MB SDRAM • microSD Flash memory card slot for Flash memory expansion, up to 32 GB 		
Interface		<ul style="list-style-type: none"> • RS-232 • USB 2.0 • Internal Ethernet, 10/100 Mbps • USB host * 1 (front side), connecting USB storage device • GPIO + Centronics • Internal Bluetooth 4.0 (dealer option) • 802.11 a/b/g/n wireless (dealer option) 		
Power		Internal universal switching power supply <ul style="list-style-type: none"> • Input: AC 100-240V, 4-2A, 50-60Hz • Output: DC 5V, 5A; DC 24V, 7A; DC 36V, 1.4A; Total 243W 		
LED/LCD		<ul style="list-style-type: none"> • 3.5" color TFT display, 320 x 240 pixel • 1 status indicator 		
Operation switch, button		<ul style="list-style-type: none"> • 6 buttons (Menu, Pause/Feed, Up, Down, Left, Right) 		
Sensors		<ul style="list-style-type: none"> • Gap transmissive sensor (position adjustable) • Black mark reflective sensor (position adjustable) • Ribbon encoder sensor • Ribbon end sensor • Head open sensor • Media cover open sensor 		
Real time clock		Standard		
Internal fonts		<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font 		
Bar code		<ul style="list-style-type: none"> • 1D bar code Code 11, Code 39, Code 49, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Standard 2 of 5, Industrial 2 of 5, Interleave 2 of 5, EAN-8, EAN-13, EAN-14, EAN-128, ITF14, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, PLANET, POSTNET, RSS-Stacked, GS1 DataBar, China Post, Telepen, LOGMARS • 2D bar code PDF-417, Micro PDF 417, Maxicode, DataMatrix, QR code, Aztec, TLC 39, RSS 		
Font and barcode rotation		0, 90, 180, 270 degree		
Printer language		TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)		
Media type		Continuous, die-cut, black mark, fan-fold, notch (outside wound)		
Media width		20 ~ 114 mm (0.8" ~ 4.5")		
Media thickness		0.076 ~ 0.305 mm (2.99 ~ 12.01 mil)		
Label length		5 ~ 25,400 mm (0.2" ~ 1,000")	5 ~ 11,430 mm (0.2" ~ 450")	5 ~ 2,540 mm (0.2" ~ 100")
Environment condition		Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing		
Safety regulation		BSMI, CE Class, FCC Class A		
Environmental concern		Comply with RoHS, WEEE		
Accessories		<ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • USB cable • Power cord 		
Limited warranty		<ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first 		
Dealer options		<ul style="list-style-type: none"> • 802.11 a/b/g/n wireless module • Internal Bluetooth 4.0 		



EZS Identtechnik GmbH
 Welserstrasse 4
 D-87463 Dietmannsried

Tel.: +49 (0)8374 / 234 44
 Fax: +49 (0)8374 / 234 45
 eMail: info@e-z-s.de
 Web: www.e-z-s.de